

Giving Shape to Ideas



• • • •

Up to 25 ppm print/copy output to keep pace with rising demands Optional dual scanning at up to 160 originals per minute Large 9" colour display with quick tablet-like touchscreen interface 3rd-party software integration with standard web browser Built-in Emperon[®] print system, universal printer drivers Simitri® HD polymerized toner for high-resolution imaging Standard 250 GB HDD for on-board document storage Meets ISO 15408 and IEEE 2600.1 security standards Power-saving design with quick recovery from sleep mode 6,650-sheet maximum capacity, tab printing support, carbon-copy printing Advanced authentication, secure print release, remote firmware updates Multiple bypass tray and detachable paper feed trays improve paper handling Finishing options for 80-page booklet-making 50-sheet stapling, 2/3-hole punch, tri-fold, and more Downloadable apps to help you work faster and smarter i-Options to add functions for working more efficiently EPEAT Gold-certified, low power consumption to cut costs Mobile printing support (AirPrint, Google Cloud Print, NFC)

bizhub C258

mfp





bizhub C258

Ideal for growing businesses, the bizhub C258 is a powerful, affordable colour MFP with superior Simitri HD image quality and fast 25 ppm print/copy output. Optional dual scanning at up to 160 opm brings information into your workflow faster - and enhanced touchscreen simplicity never slows you down.

.

System Overview	
System memory	4 GB (when UK-211 is installed)
System hard disk	250 GB standard
Interface	10BASE-T/100BASE-TX/1000BASE-T Ethernet, USB 2.0
Network protocols	TCP/IP (IPv4/IPv6), SMB, LPD, IPP, SNMP, HTTP, HTTPS
Frame types	Ethernet 802.2, Ethernet 802.3, Ethernet II, Ethernet SNAP
Document feeder (optional)	Up to 100 originals / 5.5" x 8.5" to 11" x 17" / 35-163 gsm Reversing automatic document feeder or dual scan document feeder available
Printable paper size	Scanning/Copying: up to 11" x 17" Printing: up to 11" x 17" full bleed on 12" x 18" paper Custom paper sizes Banner paper max.: 11.75" x 47.25"
Printable paper weight	52-300 gsm
Paper input capacity	Standard: 1,150 sheets / Max.: 6,650 sheets
Tray 1	500 sheets / 5.5" x 8.5" to 11" x 17" / 52-256 gsm
Tray 2	500 sheets / 5.5" x 8.5" to 12" x 18" / 52-256 gsm
Tray 3 (optional)	500 sheets / 5.5" x 8.5" to 11" x 17" / 52-256 gsm
Tray 4 (optional)	2 x 500 sheets / 5.5" x 8.5" to 8.5" x 11" / 52-256 gsm
Large capacity tray LU-302 (optional)	3,000 sheets / 8.5" x 11" / 52-256 gsm
Large capacity tray PC-410 (optional)	2,500 sheets / 8.5" x 11" / 52-256 gsm
Manual bypass	150 sheets / 4" x 6" to 12" x 18" / custom paper sizes / 50-300 gsm
Automatic duplexing	5.5" x 8.5" to 12" x 18" / 52-256 gsm
Finishing modes	Offset, group, staple, sort, punch, half-fold, tri-fold, booklet
Output capacity	Max. with finisher: 3,300 sheets Max. without finisher: 250 sheets
Stapling (optional)	Max .: 50 sheets or 48 sheets + 2 cover sheets (up to 209 gsm)
Stapling output capacity	Max.: 1,000 sheets
Tri-fold (optional)	Up to 3 sheets
Tri-fold capacity	Max.: 30 sheets (tray)
Booklet (optional)	Max.: 20 sheets or 19 sheets + 1 cover sheet (up to 209 gsm)
Booklet output capacity	Max.: 100 sheets (tray)
Copy/print volume	Max.: 80,000 pages/month ¹
Toner lifetime	Black: 28,000 pages / CMY: 26,000 pages
Imaging unit lifetime	Black: 120,000 pages / 600,000 pages (Drum / Developer) CMY: 75,000 pages / 600,000 pages (Drum / Developer)
Power consumption	120 V / 60 Hz, less than 1.5 kW (system)
System dimensions	24.2" x 27" x 31" (W x D x H)
System weight	Approx. 187.39 lb

Copier Specifications

oopier opeenications	
Copying process	Electrostatic laser copy, tandem, indirect
Toner system	Simitri® HD Polymerized Toner
Print speed (8.5" x 11")	B&W / Colour: up to 25 ppm (Portrait)
Print speed (11" x 17")	B&W / Colour: up to 15 ppm (Portrait)
Autoduplex speed	B&W / Colour: up to 25 ppm (Portrait)
(8.5" x 11")	
1st copy out time	B&W: 6.1 sec. / Colour: 7.5 sec.
Warm-up time	Approx. 20 sec. ²
Copy resolution	600 dpi x 600 dpi
Gradations	256 gradations
Multi-copy	1-9,999
Original format	Up to 11" x 17"
Magnification	25-400% in 0.1% steps, auto zooming
Copy functions	Electronic sorting, multi-job, adjustments (contrast, sharpness, image density), proof copy, interrupt mode, colour mode, separate scan, sort/group, combination, original selection, ID card copy, 2-in-1, 4-in-1

Printer Specifications

Print resolution	1800 dpi x 600 dpi, 1200 dpi x 1200 dpi
PDL	PCL 6 (XL 3.0), PCL 5c, PostScript 3 (ver. 3016), XPS
Operating systems	Windows (x32/x64): XP / Vista / 7 / 8 Windows Server (x32/x64): 2003 / 2008 / 2008 R2 ³ / 2012 ³ Macintosh OS X 10.6 or later Linux / Citrix
Printer fonts	80 PCL Latin, 137 PostScript 3
Print functions	Direct Print of PCL, PS, TIFF, XPS, PDF, encrypted PDF files and OOXML (DOCX, XLSX, PPTX), mixmedia and mixplex, "Easy Set" job programming, overlay, watermark, copy protection, carbon copy print

Printer Specifications (optional)

Print controller	Embedded Fiery IC-416
Memory/HDD	2 GB / 160 GB
PDL	PostScript 3 (ver. 3019) PCL 6/5c
Operating systems	Windows (x32/x64): XP / Vista / 7 / 8 Windows Server (x32/x64): 2003 / 2008 / 2008 R2 ³ / 2012 ³ Macintosh OS X 10.8 or later

Scanner Specifications

Scan speed	B&W / Colour: up to 160 opm with optional DF-704
Scan resolution	Max.: 600 dpi x 600 dpi
Scan modes	Scan-to-Email, Scan-to-SMB, Scan-to-FTP, Scan-to-Box, Scan-to-USB, Scan-to-WebDAV, Scan-to-DPWS, Network TWAIN scan
File formats	JPEG, TIFF, PDF, PDF/A 1a and 1b (optional), compact PDF, encrypted PDF and searchable PDF (optional), XPS, compact XPS, PPTX and searchable PPTX (optional), searchable DOCX/XLSX (optional)
Scan destinations	2,100 (shared with fax), LDAP support
Scan functions	Annotation (text/time/date) for PDF, up to 400 job programs, realtime scan preview

Fax Specifications

Fax	Super G3 (optional)
Transmission	Analog, Internet fax, Colour i-Fax, IP-Fax
Resolution	Max.: 600 dpi x 600 dpi (ultra-fine)
Compression	MH, MR, MMR, JBIG
Modem	Up to 33.6 Kbps
Destinations	2,100 (single + group)
Functions	Polling, time shift, PC-fax, receipt to confidential box, receipt to
	email/FTP/SMB, up to 400 job programs

User Box Specifications

Storable documents	Max.: 3,000 documents or 10,000 pages
Type of user boxes	Public Personal (with password or authentication) Group (with authentication)
Type of system boxes	Secure print, encrypted PDF, fax receipt, fax polling, annotation
User box functionality	Reprint, combination, download, sending (email/FTP/SMB and fax), copy box-to-box

System Features

System Features	
Security	ISO 15408 EAL IEEE 2600.1 IP filtering and port blocking SSL2, SSL3 and TSL1.0 network communication IPsec support IEEE 802.1x support FIPS 140-2 User authentication Authentication log Secure print Hard disk overwrite (8 standard types) Hard disk data encryption (AES 128) Memory data auto deletion Confidential fax receipt Print user data encryption Copy protection (Copy Guard, Password Copy) optional
Accounting	Up to 1,000 user accounts Active Directory support (user name + password + email + SMB folder) User function access definition Optional Biometric authentication (finger vein scanner) Optional ID card authentication (ID card reader)
Software	PageScope Net Care Device Manager PageScope Data Administrator PageScope Box Operator PageScope Direct Print Print Status Notifier Driver Packaging Utility Log Management Utility
¹ Maximum monthly duty	Log Management Utility cycle describes the maximum number of pages a device can output on a monthly basis.

¹ Maximum monthly duty cycle describes the maximum number of pages a device can output on a monthly basis. This specification is a guideline intended to offer a comparison of durability as it relates to the entire Konica Minolta MFP and printer product line so that the appropriate device can be placed in order to meet customer needs.
 ² Warm-up time may vary depending on the operating environment and usage.
 ³ Supports x64 only.

AU-102 Biometric	Finger vein scanner
authentication	
AU-204H Magnetic stripe card reader	Requires WT-506 Working table
AU-205H Universal	Various ID card technologies
ID card reader	÷
AU-211 CA/PIV	Requires WT-506 Working table
solution DF-629	Deversing automatic desumant feeder, especity 100 originals
Dr-629 Document feeder	Reversing automatic document feeder, capacity 100 originals
DF-704	Dual scan automatic document feeder, capacity 100 originals
Document feeder	
DK-510 Copier desk	Provides storage space for print media and other materials
FK-514 Fax board	Super G3 fax, digital fax functionality
FK-515 Fax board FS-533 Staple finisher	Super G3 fax, digital fax functionality, lines 3 and 4 support
FS-534 Staple finisher	50-sheet stapling, 500 sheets max. output 50-sheet stapling, 3,300 sheets max. output
FS-534 + SD-511	50-sheet staple finisher, 20-sheet booklet finisher,
Booklet finisher	3,300 sheets max. output
HD-524 Hard disk	Hard disk mirroring, 250 GB
IC-416 Fiery	Embedded image controller for graphics-intensive applications
image controller	Conception for four output at-
JS-506 Job separator KH-102	Separation for fax output, etc. To place USB keyboard
KH-102 Keyboard holder	TO PIACE USB REYDOATD
KP-101 10-Key pad	For use instead of touchscreen
LK-102 v3	PDF/A, PDF encryption, digital signature
PDF enhancements	
LK-104 v3	Provides voice guidance functions
Voice guidance	0
LK-105 v4 OCR text recognition	Searchable PDF
LK-106	Supports native barcode printing
Barcode fonts	oupporte natio saloodo printing
LK-107	Supports native Unicode printing
Unicode fonts	
LK-108 OCR A and B fonts	Supports native OCR A and B font printing
LK-110 v2 Enhanced	Generates various file formats incl. DOCX, XLSX and combines
image support	LK-102 (encrypted PDF) + LK-105 (searchable PDF/OCR functionality)
LK-111	Print data compression for reduced network impact
ThinPrint [®] Client	
LU-302	8.5" x 11", 3,000 sheets / 52-256 gsm
Large capacity unit MK-730 Mount kit	Banner paper guide
MK-735 Mount kit	Installation kit for ID card reader
MK-742 Mount kit	Installation kit for FK-515 fax board
OC-511 Original cover	Cover instead of auto document feeder
PC-110	5.5" x 8.5" to 11" x 17", 500 sheets, 52-256 gsm
Universal tray (x1)	
PC-210	5.5" x 8.5" to 11" x 17", 2 x 500 sheets, 52-256 gsm
Universal tray (x2) PC-410	8.5" x 11", 2,500 sheets, 52-256 gsm
PG-410 Large capacity tray	0.0 ATT, 2,000 SHEELS, 02-200 USHI
PK-519 Punch kit	2/3-hole punching, autoswitching
for FS-533	
PK-520 Punch kit	2/3-hole punching, autoswitching
for FS-534	Derived for the EQ EQ4 and EQ EQ4 _ QD E44
RU-513 Relay unit	Required for the FS-534 and FS-534 + SD-511
SC-508 Security kit SK-602 Staple kit	Copy Guard function (2x required when DF-704 is installed) Added stapling functionality kit
SR-602 Staple Kit	Added fax stamp capability kit
UK-211	2 GB memory expansion, required for most i-Options, registered
	overlay, and concurrent use of web browser and certain other
	functions, including stamp print, watermark, date/time print,
IIV 010 Winclose I AN	header/footer, image overlay and management number
UK-212 Wireless LAN	Wireless LAN to network connector
	Fiery controller interface card
VI-508 Interface kit for IC-416	Fiery controller interface card
VI-508 Interface kit	Fiery controller interface card Authentication device placement

Co A



www.konicaminolta.ca

f 🕑 ወ in

KONICA MINOLTA BUSINESS SOLUTIONS (CANADA) LTD. 369 Britannia Road East, Mississauga, ON L4Z 2H5

© 2016 KONICA MINOLTA BUSINESS SOLUTIONS (CANADA) LTD. All rights reserved. Reproduction in whole or in part without written permission is prohibited. KONICA MINOLTA, the KONICA MINOLTA logo, Count on Konica Minolta, bizhub, PageScope, and Giving Shape to Ideas are registered trademarks or trademarks or KONICA MINOLTA, INC. Trademarks of the Canadian Breast Cancer Foundation, used under licence. All other product and brand names are trademarks or registered trademarks of their respective companies or organizations. All features and functions described here may not be available on some products. Design and specifications are subject to change without notice.



ltem #: C258SS 01/16 - P