

## imageRUNNER ADVANCE 6500 III Series

Black-and-White | Mid- to High-Volume | Multifunction

Print up to 75 ppm (BW)

Scan up to 240/220 ipm (300 dpi) (BW, colour, duplex)

Print up to 11" × 17"

7,700-sheet maximum paper capacity

Canon's comprehensive portfolio of imageRUNNER ADVANCE multifunction printers and integrated solutions can help **simplify** the end user experience and management of technology; better **control** sensitive information and print-related costs; and help ensure that technology investments proactively **evolve** with changing needs.



### WORKFLOW EFFICIENCY

- 10.1" intuitive touchscreen with smartphone-like usability.
- A unique, customized experience tailored to individual preferences with My ADVANCE.
- Supports mobile solutions and integration with many popular cloud services like Google Drive and Box.<sup>1</sup>
- Scan and convert documents to searchable digital files in a variety of file formats.
- Integration with Canon and various third-party software with embedded application platform.



### SECURITY

- Advanced standard security feature set to help safeguard sensitive information and assist in regulatory compliance.
- Integrates with existing, third-party Security Information and Event Management (SIEM) systems to help provide real-time comprehensive insights into potential threats to the network and printers.
- Technology to verify that the device boot process, firmware, and applications initialize without alterations or tampering.
- Security policy settings can be controlled with a dedicated password, configured from a central location, and exported to other supported devices.
- Control access to the device and specific features, using a host of flexible authentication methods—PIN code, user name/password, or card access.<sup>2</sup>



### QUALITY AND RELIABILITY

- Canon's signature reliability and engine technologies help keep productivity high and minimize the impact on support resources.
- Outstanding imaging technologies and toner allow for crisp text and consistent images in rich black-and-white tones.
- Designed to achieve maximum uptime with status notifications to help keep supplies replenished and intuitive maintenance videos for consumables replacement.
- imageRUNNER ADVANCE models have received many awards and recognition from leading industry analysts, often referencing strong reliability.



## DEVICE AND FLEET MANAGEMENT

- Designed for quick, easy deployment.
- Remote diagnostics and parts life management for proactive maintenance and rapid fixes.
- Easy and intuitive to monitor device status and consumable levels, turn off devices remotely, observe meter readings, manage settings, and implement security policies.
- Common firmware and regular updates with Unified Firmware Platform (UFP) for continuous improvements and consistency across a fleet.



## COST MANAGEMENT

- Track and assess print, copy, scan, and fax usage and allocate costs to departments or projects.
- Apply print policies and restrict usage by user to help reduce unnecessary printing and contribute to cost efficiency.
- Standard cloud-based solution provides a centralized dashboard with up-to-the-minute insights into printer activity.
- Upgrade to uniFLOW server or cloud-based solutions for full accounting and reporting for compatible Canon and third-party devices, pull printing, job routing, and powerful scan workflows.



## SUSTAINABILITY

- A combination of fusing technologies and low-melting-point toner minimizes power requirements and helps achieve low energy consumption.
- Encourage environmentally-conscious work practices by enabling multiple settings that can help save paper and energy.
- ENERGY STAR® certified.

## CONFIGURATION OPTIONS



### STAPLE FINISHER-V2

- 3-tray, 3,500-sheet capacity
- Corner and double stapling up to 65 sheets
- Supports Staple-free Stapling and Staple On Demand
- Supports optional internal 2/3-hole puncher (2/3 Hole Puncher Unit-A1)



### BOOKLET FINISHER-V2

- 3-tray, 3,500-sheet capacity
- Corner and double stapling up to 65 sheets
- Booklet-making up to 20 sheets and saddle-folding up to 3 sheets
- Supports Staple-free Stapling and Staple On Demand
- Supports optional internal 2/3-hole puncher (2/3 Hole Puncher Unit-A1)



### DOCUMENT INSERTION/ FOLDING UNIT-J1

- Insert pre-printed sheets
- Up to 11" x 17"
- 1-tray, 100-sheet capacity
- Z-fold, C-fold



### DOCUMENT INSERTION UNIT-P1

- Insert pre-printed sheets
- Up to 11" x 17"
- 1-tray, 100-sheet capacity



### COPY TRAY-R2



### UPRIGHT CONTROL PANEL-HI



### UTILITY TRAY-B1



### POD DECK LITE-C1

- 3,500-sheet capacity
- 14 lb. Bond to 140 lb. Index
- Supports up to 11" x 17"
- User adjustable



### imagePASS-Y3

- Delivers fast processing speed, outstanding image quality, and time-saving workflow
- Integrates print production workflows with EFI™ management information systems, Web-to-Print systems, and popular prepress workflows for end-to-end automation
- Communicates with the full suite of optional uniFLOW modules



### PAPER DECK UNIT-E1

- 3,500-sheet capacity
- 14 lb. Bond to 140 lb. Index
- Supports LTR

# SPECIFICATIONS

## Main Unit

### Type

Monochrome Laser Multifunctional

### Core Functions

Standard: Print, Copy, Scan, Send, Store  
Optional: Fax

### Processor

Canon Dual Custom Processor (Shared)

### Control Panel

Standard: 10.1" TFT LCD WSVGA Colour Flat-panel  
Optional: 10.4" TFT LCD SVGA Colour Upright-panel

### Memory

3.0 GB RAM

### Hard Disk Drive

Standard: 250 GB  
Maximum: 1 TB

### Interface Connection

#### Network

Standard: 1000Base-T/100Base-TX/10Base-T,  
Wireless LAN (IEEE 802.11 b/g/n)

Optional: NFC, Bluetooth Low Energy

#### Others

Standard: USB 2.0 x2 (Host), USB 3.0 x1 (Host),  
USB 2.0 x1 (Device)

Optional: Serial Interface, Copy Control Interface

### Paper Capacity

Standard: 4,200 Sheets  
Maximum: 7,700 Sheets

### Paper Sources (LTR, 20 lb. Bond)

Standard: Dual 1,500-sheet Paper Drawers, Dual  
550-sheet Paper Cassettes, 100-sheet  
Stack Bypass

Optional: 3,500-sheet Paper Deck  
(POD DECK LITE-C1 or  
PAPER DECK UNIT-E1)

### Paper Output Capacity (LTR, 20 lb. Bond)

With Copy Tray: 250 Sheets  
With External: 3,500 Sheets  
Finishers:

### Finishing Capabilities

With External: Collate, Group, Offset, Staple, Staple  
Finishers: On Demand, Staple-free Staple, Booklet,  
Hole Punch, Document Insertion, C and Z  
Folding

### Supported Media Types

Paper Drawers (1/2): Thin, Plain, Recycled, Colour, Heavy,  
Pre-punched, Letterhead, Bond  
Paper (3/4): Thin, Plain, Recycled, Colour, Heavy,  
Cassettes (3/4): Pre-punched, Letterhead, Bond, Tab.  
Stack Bypass: Thin, Plain, Recycled, Colour, Heavy,  
Pre-punched, Bond, Transparency, Labels,  
Letterhead, Tab, Tracing<sup>3</sup>  
POD DECK LITE-C1: Thin, Plain, Recycled, Colour, Heavy, Pre-  
punched, Letterhead, Bond, Transparency,  
Labels, Tab  
PAPER DECK UNIT-E1: Thin, Plain, Recycled, Colour, Heavy,  
Pre-punched, Letterhead, Bond

### Supported Media Sizes

Paper Drawers Letter  
(1/2):  
Paper Cassettes 11" x 17", Legal, Letter, Letter-R, Executive,  
(3/4): Statement-R, Custom Size (5-1/2" x 7-1/8" to  
11-3/4" x 19-1/4")  
Stack Bypass: 11" x 17", Legal, Letter, Letter-R, Executive,  
Statement-R, Custom Size  
(4" x 5-7/8" to 11-3/4" x 19-1/4"), Free Size  
(4" x 7-1/8" to 11-3/4" x 19-1/4")  
POD DECK LITE-C1: 11" x 17", Legal, Letter, Letter-R, Executive,  
Statement-R, Custom Size (5-1/2" x 7-1/8" to  
11-3/4" x 19-1/4")  
PAPER DECK UNIT-E1: Letter

### Supported Media Weights

Paper Decks/ Cassettes: 14 lb. Bond to 80 lb. Cover (52 to 220 g/m<sup>2</sup>)  
Stack Bypass: 14 lb. Bond to 140 lb. Index (52 to 256 g/m<sup>2</sup>)  
Duplexing: 14 lb. Bond to 80 lb. Cover (52 to 220 g/m<sup>2</sup>)

### Warm-up Time

From Power On: Approx. 30 Seconds<sup>4</sup>  
From Sleep: Approx. 30 Seconds<sup>5</sup>  
Mode:  
Quick Start-up: Approx. 4 Seconds<sup>6</sup>  
Mode:

### Dimensions (W x D x H)

26-3/8" x 30-5/8" x 48"  
(670 mm x 779 mm x 1220 mm)

### Installation Space (W x D)

Basic: Stack Bypass Extended+ Cassette Drawers  
open + Copy Tray:  
60-3/8" x 53-1/4" (1533 mm x 1353 mm)  
Fully Configured: Booklet Finisher + Paper Deck + Insertion  
and Folding Unit + Puncher Unit + Cassette  
Drawers open:  
95-7/8" x 53-1/4" (2436 mm x 1353 mm)

### Weight

Approx. 515.9 lb. (234 kg)<sup>7</sup>

## Print Specifications

### Print Speed

6575i III: Up to 75 ppm (Letter)  
Up to 58 ppm (Letter-R)  
Up to 45 ppm (Legal)  
Up to 37 ppm (11" x 17")  
6565i III: Up to 65 ppm (Letter)  
Up to 50 ppm (Letter-R)  
Up to 39 ppm (Legal)  
Up to 32 ppm (11" x 17")  
6555i III: Up to 55 ppm (Letter)  
Up to 43 ppm (Letter-R)  
Up to 39 ppm (Legal)  
Up to 32 ppm (11" x 17")

### Print Resolution (dpi)

1200 x 1200, 600 x 600

### Standard Page Description Languages

UFR III, PCL<sup>®</sup>6, Adobe<sup>®</sup> PS<sup>®</sup> 3

### Direct Print

Available from USB, Advanced Box, Remote UI,  
and Web Access<sup>8</sup>

### Supported File Types

PDF, TIFF, JPEG, EPS,<sup>9</sup> XPS

### Printing from Mobile and Cloud

A range of software and MEAP-based solutions are  
available to provide printing from mobile devices or  
Internet-connected devices and cloud-based services  
depending on your requirements.

### Fonts

PCL fonts: 93 Roman, 10 Bitmap fonts, 2 OCR  
fonts, Andalé Mono WT J/K/S/T (Japanese,  
Korean, Simplified and Traditional Chinese)<sup>10</sup>,  
Barcode Fonts<sup>11</sup>  
PS fonts: 136 Roman

### Operating System<sup>12</sup>

UFR III: Server 2008/Windows 7/Server 2008 R2/  
Server 2012/Windows 8.1/Server 2012 R2/  
Windows 10/Server 2016, MAC OS X (10.9  
or later)  
PCL: Server 2008/Windows 7/Server 2008 R2/  
Server 2012/Windows 8.1/Server 2012 R2/  
Windows 10/Server 2016  
PS: Server 2008/Windows 7/Server 2008 R2/  
Server 2012/Windows 8.1/Server 2012 R2/  
Windows 10/Server 2016, MAC OS X  
(10.9 or later)  
PPD: MAC OS X (10.3.9 or later), Windows 7 / 8.1 / 10

### Print Features

Suspend Job Timeout, Subset Finishing (PS only), Profile  
Settings, Secured Print, Watermark, Header/Footer, Page  
Layout, Two-sided Printing, Collating, Booklet Printing,  
Grouping, Mixed Paper Sizes/Orientations, Offsetting,  
Front/Back Covers, Toner Reduction, Poster Printing

## Copy Specifications

### Copy Speed

6575i III: Up to 75 ppm (Letter)  
Up to 58 ppm (Letter-R)  
Up to 45 ppm (Legal)  
Up to 37 ppm (11" x 17")  
6565i III: Up to 65 ppm (Letter)  
Up to 50 ppm (Letter-R)  
Up to 39 ppm (Legal)  
Up to 32 ppm (11" x 17")  
6555i III: Up to 55 ppm (Letter)  
Up to 43 ppm (Letter-R)  
Up to 39 ppm (Legal)  
Up to 32 ppm (11" x 17")

### First-Copy-Out Time (Letter)

6575i III: As fast as 3.1 seconds  
6565i III: As fast as 3.3 seconds  
6555i III: As fast as 3.3 seconds

### Copy Resolution (dpi)

Reading: 600 x 600  
Printing: 1200 x 1200

### Multiple Copies

Up to 9,999 Copies

### Magnification

25%-400% (1% Increments)

### Preset Reductions

25%, 50%, 64%, 73%, 78%

### Preset Enlargements

121%, 129%, 200%, 400%

### Basic Copy Features

Preset Reduction/Enlargement Ratios by Area, Paper  
Setting, Previous Settings, Favorite Settings, Finishing,  
Two-Sided, Density Adjustment, Original Type Selection,  
Interrupt Mode, Setting Confirmation/Cancel

### Special Copy Features

Book to Two Pages, Two-sided Original, Finishing, Booklet,  
Job Build, N on 1, Add Cover, Insert Sheets, Different Size  
Originals, Density Adjustment, Original Type Selection,  
Transparency Cover Sheets, Page Numbering, Copy Set  
Numbering, Sharpness, Erase Frame, Secure Watermark,  
Print Date, Shift, Gutter, Print & Check, Negative/Positive,  
Repeat Images, Merge Job Blocks, Job Done Notice, Mirror  
Image, Print on Tab, Store in Mail Box, Superimpose Image,  
Cascade Copy, Copy ID Card, Detect Feeder Multi Sheet  
Feed, Free Size Original, Skip Blank Originals

## Scan Specifications

### Type

Colour Platen and Single-pass Duplexing Automatic  
Document Feeder

### Document Feeder Paper Capacity

300 Sheets (20 lb. Bond)

### Document Feeder Supported Media Sizes

11" x 17", Legal, Letter, Letter-R, Statement, Statement-R

### Document Feeder Supported Media Weights

BW Original: 13 lb. Bond to 80 lb. Cover  
(50 to 220 g/m<sup>2</sup>)  
Colour Original: 17 lb. Bond to 80 lb. Cover  
(64 to 220 g/m<sup>2</sup>)

### Platen Acceptable Originals

Sheet, Book, 3-Dimensional Objects [Height: up to 2"  
(50 mm), Weight: up to 4.4 lb. (2 kg)]  
Max. Platen  
Scanning Size: 11-3/4" x 17" (297 mm x 431.8 mm)

### Pull Scan

Colour Network ScanGear2 for both Twain and WIA  
Supported OS: Windows 7/8.1/10  
Server 2008/Server 2008 R2/Server 2012/  
Server 2012 R2/Server 2016

### Scan Resolution (dpi)

600 x 600, 400 x 400, 300 x 300, 200 x 400, 200 x 200,  
200 x 100, 150 x 150, 100 x 100

### Scan to Mobile Devices and Cloud-based Services

A range of solutions is available to provide scanning to  
mobile devices and cloud-based services depending on  
your requirements.

### Scan Speed (Letter)

Single-sided Scanning  
BW: 120 ipm (300 dpi)/120 ipm (600 dpi)  
Colour: 120 ipm (300 dpi)

### Double-sided Scanning

BW: 240 ipm (300 dpi)/150 ipm (600 dpi)  
Colour: 220 ipm (300 dpi)

## Send Specifications

### Destination

Email/Internet Fax (SMTP), SMB, FTP, WebDAV, Mail Box,  
Super G3 Fax (Optional), IP Fax (Optional)

### Address Book

LDAP (2,000)/Local (1,600)/Speed dial (200)

### Send Resolution (dpi)

600 x 600, 400 x 400, 300 x 300, 200 x 400, 200 x 200,  
200 x 100, 150 x 150, 100 x 100

## Communication Protocol

File: FTP, SMB v3.0, WebDAV  
Email: SMTP, POP3, I-Fax (Simple, Full)

## File Format

Standard: TIFF, JPEG, PDF (Compact, Searchable, Apply policy, Optimize for Web, PDF A/1-b, Encrypted, Device Signature), XPS (Compact, Searchable, Device Signature), Office Open XML (PowerPoint, Word)  
Optional: PDF (Trace & Smooth, User Signature), XPS (User Signature)

## Universal Send Features

Original Type Selection, Two-sided Original, Book to Two Pages, Different-size Originals, Density Adjustment, Sharpness, Copy Ratio, Erase Frame, Job Build, Delayed Send, Preview, Job Done Notice, File Name, Subject/Message, Reply-to, Email Priority, TX Report, Original Content Orientation, Skip Blank Originals, Multi Sheet Feed Detection

## Fax Specifications (Optional)

### Modem Speed

Super G3: 33.6 Kbps  
G3: 14.4 Kbps

### Compression Method

MH, MR, MMR, JBIG

### Resolution (dpi)

400 x 400, 200 x 400, 200 x 200, 200 x 100

### Sending/Recording Size

Statement-R to 11" x 17"

### Fax Memory

Up to 30,000 Pages

### Speed Dials

Max. 200

### Group Dials/Destinations

Max. 199 Dials

### Sequential Broadcast

Max. 256 Addresses

### Memory Backup

Yes

### Fax Features

Original Type Selection, Two-sided Original, Book to Two Pages, Different-size Originals, Density for Scanning, Sharpness, Copy Ratio, Erase Frame, Job Build, Sender's Name (TTI), Selecting the Telephone Line, Direct Send, Delayed Send, Preview, Job Done Notice, TX Report, Multi Sheet Feed Detection

## Store Specifications

### Mail Box (Number Supported)

100 User In-boxes, 1 Memory RX In-box, 50 Confidential Fax In-boxes, 30,000 Maximum Pages Stored

### Advanced Box

Communication Protocol: SMB or WebDAV  
Supported Windows (Windows 7/8.1/10)  
Client PC:  
Concurrent Connections (Max.):  
SMB: 64  
WebDAV: 3 (Active Sessions)

### Advanced Box Available Disc Space

Approx. 16 GB (Standard HDD)  
Approx. 480 GB (With Optional 1 TB HDD)

### Advanced Box Features

Authentication for Advanced Box Log-in, Sort Function, Printing a PDF File with a Password

### Memory Media

Standard: USB

## Security Specifications

### Authentication

Standard: Universal Login Manager, uniFLOW Online Express,<sup>13</sup> User Authentication, Department ID Authentication, (Device and Function Level Log-in), Access Management System  
Optional: uniFLOW

### Data

Standard: Trusted Platform Module (TPM), Hard Disk Password Lock, Hard Disk Drive Erase, Mail Box Password Protection, Hard Disk Drive Encryption (FIPS140-2 Validated), Verify System at Startup  
Optional: Hard Disk Drive Mirroring, Hard Disk Drive Removal, IEEE 2600.2 Common Criteria Certification, Data Loss Prevention (Requires uniFLOW)

### Network

Standard: Encrypted Secure Print, IP/Mac Address Filtering, IPsec, TLS Encrypted Communication, SNMP V3.0, IEEE 802.1X, IPv6, SMTP Authentication, POP Authentication before SMTP, S/MIME, SIEM Integration

### Document

Standard: Secure Watermark, Secure Print, Adobe LiveCycle® Rights Management ES2.5 Integration, Encrypted PDF, Encrypted Secure Print, Device Signature  
Optional: User Signature, Document Scan Lock

## Environmental Specifications

### Operating Environment

Temperature: 50 to 86 °F  
Humidity: 20 to 80 % RH (Relative Humidity)

### Power Requirements

120-127 V AC, 60 Hz, 16 A

### Plug (Main Unit)

NEMA 5-20P

### Power Consumption

Maximum: Approx. 2,032 W  
Standby: Approx. 237.3 W<sup>14</sup>  
Sleep mode: 0.9 W<sup>15</sup>

### Typical Electricity Consumption (TEC) Rating:

iR ADV 6575i III: 6.3 kWh  
iR ADV 6565i III: 5.8 kWh  
iR ADV 6555i III: 5.2 kWh

### Standards

ENERGY STAR® Certified

## Consumables

### Toner

GPR-38 Black Toner

### Toner Yield (Estimated @ 6% Coverage)

56,000 Images

<sup>1</sup> Subscription to a third-party cloud service required. Subject to third-party cloud service providers' terms and conditions.

<sup>2</sup> Requires additional option.

<sup>3</sup> Some types of tracing paper cannot be used.

<sup>4</sup> Time from device power-on, until copy ready (not print reservation).

<sup>5</sup> Time from exiting Sleep mode to when printing is operational.

<sup>6</sup> Time from device power-on to when key operations can be performed on the touch panel.

<sup>7</sup> Includes Main Unit, ADF, and Consumables.

<sup>8</sup> PDF print from Websites is supported.

<sup>9</sup> EPS can be printed directly only from the Remote User Interface.

<sup>10</sup> Requires the optional PCL International Font Set-A1.

<sup>11</sup> Requires the optional Barcode Printer Kit-D1.

<sup>12</sup> Other operating systems and environments including AS/400, UNIX, Linux and Citrix may be supported. Some of these solutions are chargeable. SAP Device Types are available via the SAP Market Place. For more information, contact your sales representative.

<sup>13</sup> No charge for this solution; however activation is required.

<sup>14</sup> Standby Reference Value: measured one unit.

<sup>15</sup> 0.9 W sleep mode not available in all circumstances due to certain settings.

For detailed specifications and a comprehensive list of optional accessories, see the [imageRUNNER ADVANCE 6500 III Series Specifications document](#).

 WWW.CANON.CA





As an ENERGY STAR® Partner, Canon U.S.A., Inc. has certified these models as meeting the ENERGY STAR guidelines for energy efficiency. The ENERGY STAR mark is a registered mark in Canada. AirPrint and the AirPrint logo are trademarks of Apple Inc. Canon, imageRUNNER, imageWARE, imagePASS, and the GENUINE logo are registered trademarks of Canon Inc. in Canada and may also be registered trademarks or trademarks in other countries. All other referenced product names and marks are trademarks of their respective owners and are hereby acknowledged. "III" indicates that this model has been upgraded to new system software and includes additional security features as standard. Canon products offer certain security features, yet many variables can impact the security of your devices and data. Canon Canada Inc. does not warrant that use of its features will prevent security issues. Nothing herein should be construed as legal or regulatory advice concerning applicable laws; customers must have their own qualified counsel determine the feasibility of a solution as it relates to regulatory and statutory compliance. All features presented in this brochure may not apply to all Series and/or products and may be optional; please check with a Canon Sales Representative or a Canon Authorized Dealer for details. All printer output images are simulated. Products are shown with optional accessories. Specifications and availability subject to change without notice. Each customer must have its own qualified counsel determine the advisability of a particular solution as it relates to regulatory or statutory compliance. Not responsible for typographical errors.

©2019 Canon Canada Inc. All rights reserved.

0216W109

To learn about Canon's many awards, visit [www.canon.ca/awards](http://www.canon.ca/awards)

 UNIFIED FIRMWARE PLATFORM



 CANON GENUINE TONER, CARTRIDGE & PARTS

