

imageRUNNER ADVANCE DX C357iF Series

Colour
Compact
Multifunction

Print up to 36 ppm (BW/colour)

Scan up to 200 ipm (300 dpi) (BW/colour, duplex)

Print up to 8-1/2" × 14"

2,300-sheet maximum paper capacity

Canon's comprehensive portfolio of imageRUNNER ADVANCE DX multifunction printers and integrated solutions can help **simplify** the end user experience and management of technology, better **control** sensitive information and print-related costs, and help ensure that technology investments proactively **evolve** with changing needs.



WORKFLOW EFFICIENCY

- 10.1" intuitive touch screen with smartphone-like usability.
- A unique, customized experience tailored to individual preferences using My ADVANCE.
- Supports mobile solutions and integration with many popular cloud services like Google Drive.¹
- Scan and convert documents to searchable digital files in a variety of file formats.
- Integration with Canon and various third-party software with embedded application platform.
- Hot Folders allow users to drag and drop a file into a hot folder and automatically print with pre-defined settings such as number of copies and finishing requirements.



SECURITY

- Advanced standard security feature set to help safeguard sensitive information and assist in regulatory compliance.
- Integrates with existing, third-party SIEM*² systems to help provide real-time, comprehensive insights into potential threats to the network and printers.
- Technology to verify that the device boot process, firmware, and applications initialize without alteration at startup. McAfee Embedded Control³ utilizes a whitelist to protect against malware and tampering of firmware and applications.
- Security policy settings can be controlled with a dedicated password, configured from a central location, and exported to other supported devices.
- Control access to the device and specific features, using a host of flexible authentication methods—PIN code, user name/password, or card access.⁴



QUALITY AND RELIABILITY

- Canon's signature reliability and engine technologies help keep productivity high and minimize the impact on support resources.
- Outstanding imaging technologies and toner allow for consistently striking images, thanks to Canon's V² colour profile.
- Designed to achieve maximum uptime with status notifications that help keep supplies replenished plus intuitive maintenance videos for consumables replacement.
- imageRUNNER ADVANCE models have received many awards and recognition from leading industry analysts, often referencing strong reliability.

* Security Information and Event Management



DEVICE AND FLEET MANAGEMENT

- Designed for quick, easy deployment.
- Remote diagnostics and parts life management for proactive maintenance and rapid fixes.
- Easy and intuitive to monitor device status and consumable levels, turn off devices remotely, observe meter readings, manage settings, and implement security policies.
- Common firmware and regular updates with Unified Firmware Platform (UFP) for continuous improvements and consistency across a fleet.



COST MANAGEMENT

- Track and assess print, copy, scan, and fax usage and allocate costs to departments or projects.
- Apply print policies and restrict usage by user to help reduce unnecessary printing and contribute to cost efficiency.
- Standard cloud-based solution provides a centralized dashboard with up-to-the-minute insights into printer activity.
- Upgrade to uniFLOW server or cloud-based solutions for full accounting and reporting for compatible Canon and third-party devices, pull printing, job routing, and powerful scan workflows.



SUSTAINABILITY

- A combination of fusing technologies and low-melting-point toner minimizes power requirements and helps achieve low energy consumption.
- Encourage environmentally conscious work practices by enabling multiple settings that can help save paper and energy.
- ENERGY STAR® certified.

CONFIGURATION OPTIONS



SPECIFICATIONS

Main Unit

Type

Colour Laser Multifunctional

Core Functions

Print, Copy, Scan, Send, Store, Fax

Processor

1.75GHz Dual Core Processor

Control Panel

10.1" TFT LCD WSVGA Colour Touch-panel

Memory

3.0 GB RAM

Hard Disk Drive

320 GB (available disk space: 200 GB)

Interface Connection

Network: 1000Base-T/100Base-TX/10Base-T,
Wireless LAN (IEEE 802.11 b/g/n)

Optional: NFC, Bluetooth Low Energy

Others

Standard: USB 2.0 x1 (Host), USB 3.0 x1 (Host),
USB 2.0 x1 (Device)

Optional: Serial Interface, Copy Control Interface

Paper Capacity (LTR, 20 lb. Bond)

Standard: 650 Sheets

Maximum: 2,300 Sheets

Paper Sources (LTR, 20 lb. Bond)

Standard: 550-sheet Paper Cassette, 100-sheet
Multi-Purpose Tray

Optional: 550-sheet Paper Cassette (CASSETTE
MODULE-AE1), 550-sheet Paper Cassette
with cabinet (CASSETTE FEEDING UNIT-
AJ1), Triple 550-sheet Paper Cassettes
(CASSETTE FEEDING UNIT-AK1)

Paper Output Capacity (LTR, 20 lb. Bond)

Standard: 250 Sheets

Maximum: 500 Sheets (with STAPLE FINISHER-Z1)

Finishing Capabilities

Standard: Collate, Group

With External

Finisher: Collate, Group, Offset, Staple

Supported Media Types

Multi-Purpose Thin, Plain, Heavy, Recycled, Colour,

Tray: Transparency, Pre-punched, Bond,
Label, Envelope

Paper Thin, Plain, Heavy, Recycled, Colour,

Cassette: Pre-punched, Bond, Envelope

Supported Media Sizes

Standard Size: Legal, Letter, Executive, Statement

Custom Size: 3-7/8" x 5-7/8" to 8-1/2" x 14"
(98.0 x 148.0 mm to 216.0 x 355.6 mm)

Envelopes: COM10 No.10, Monarch, DL, ISO-C5

Envelope 3-7/8" x 5-7/8" to 8-1/2" x 14"

Custom Size: (98.0 x 148.0 mm to 216.0 x 355.6 mm)

Paper Cassette

Standard size: Legal, Letter, Executive, Statement

Custom Size: 3-7/8" x 7-1/2" to 8-1/2" x 14"
(98.0 x 190.5 mm to 216.0 x 355.6 mm)

Envelopes: COM10 No.10, Monarch, DL, ISO-C5

Supported Media Weights

Cassettes: 16 lb. Bond to 60 lb. Cover (60 to 163 g/m²)

Multi-Purpose 16 lb. Bond to 80 lb. Cover (60 to 220 g/m²)

Tray:

Duplexing: 16 lb. Bond to 60 lb. Cover (60 to 163 g/m²)

Print/Copy Speed (BW and Colour)

C357iF: Up to 36 ppm (Letter);

Up to 29 ppm (Legal)

C257iF: Up to 26 ppm (Letter);

Up to 21 ppm (Legal)

Warm-up Time

From Power Approx. 10 Seconds⁵

On:

From Sleep Approx. 10 Seconds⁶

Mode:

Quick Startup Approx. 4 Seconds⁷

Mode:

Dimensions (W x D x H)

Standard 20-1/2" x 25-7/8" x 25-1/8"

(Desktop): (519 mm x 658 mm x 638 mm)

Installation Space (W x D)

Basic: 33-1/2" x 35-3/4" (852 mm x 908 mm)
(with Paper Cassette Open + Multi-Purpose
Tray Extended)

Fully 55-3/8" x 35-3/4" (1407 mm x 908 mm)

Configured: (with Staple Finisher-Z1 + Paper Cassette
Open + Multi-Purpose Tray Extended)

Weight⁸

Standard

(Desktop): Approx. 108 lb. (49 kg)

Print Specifications

Print Resolution (dpi)

1200 x 600

Standard Page Description Languages

UFR II, PCL[®]6, Adobe[®] PS[®] 3

Supported File Types

PDF, TIFF, JPEG, EPS, XPS

Printing from Mobile Devices and Cloud-based Services

A range of standard and optional software and MEAP-based solutions (including AirPrint, Mopria, Google Cloud Print, Canon PRINT Business, and uniFLOW Online) are available to provide printing from mobile devices or internet-connected devices and cloud-based services depending on your requirements. Please contact your sales representative for further information.

Fonts

PCL: 93 Roman, 10 Bitmap fonts, 2 OCR fonts,
Andalé Mono WT J/K/S/T (Japanese,
Korean, Simplified and Traditional Chinese)⁹,
Barcode Fonts¹⁰

PS:

136 Roman

Operating System¹¹

UFR II/PS: Windows[®] 7/8.1/10/Server 2008/
Server 2008 R2/Server 2012/
Server 2012 R2/Server 2016/
Server 2019, Mac OS X (10.10 or later)

PCL: Windows[®] 7/8.1/10/Server 2008/Server
2008 R2/Server 2012/Server 2012 R2/
Server 2016/Server 2019

PPD: Windows[®] 7/8.1/10, Mac OS X (10.9 or later)

Copy Specifications

First-Copy-Out Time (LTR)

C357iF: As fast as 5.1 seconds (BW)/

6.9 seconds (Colour)

C257iF: As fast as 6.9 seconds (BW)/

9.4 seconds (Colour)

Copy Resolution (dpi)

With Platen: 600 x 600

With DADF: 300 x 600

Multiple Copies

Up to 999

Magnification

25%-400% (1% Increments)

Preset Reduction/Enlargement:

25%, 50%, 64%, 78%, 100% (1:1), 129%, 200%, 400%

Scan Specifications

Type

Single-pass Duplexing Automatic Document Feeder¹²

Document Feeder Paper Capacity

Up to 100 Sheets (20 lb. Bond)

Document Feeder Supported Media Sizes

Legal, Letter, Statement

Custom Size: 1-7/8" x 5" to 8-1/2" x 14" (48.0 mm x
128.0 mm to 216.0 mm x 355.6 mm)

Business Card: 1-7/8" x 3-3/8" to 2-1/8" x 3-5/8" (48.0 mm x
85.0 mm to 55.0 mm x 91.0 mm)

Document Feeder Supported Media Weights

One-Sided 13.3 to 34 lb. Bond (50 to 128 gsm) (BW), 17 to

Scanning: 34 lb. Bond (64 to 128 gsm) (CL)

Two-Sided 13.3 to 34 lb. Bond (50 to 128 gsm) (BW), 17 to

Scanning: 34 lb. Bond (64 to 128 gsm) (CL)

Note:

Business Card: 21.3 lb bond to 80 lb cover (80 to 220 gsm)

Platen Acceptable Originals

Sheet, Book, 3-Dimensional Objects

Pull Scan

Colour Network ScanGear2 for both Twain and WIA

Supported OS: Windows[®] 7/8.1/10/Server 2008/
Server 2008 R2/Server 2012/
Server 2012 R2/Server 2016

Scan Resolution (dpi)

Scan for Copy: 600 x 600

Scan for Send: (Push) 600 x 600 (SMB/FTP/WebDAV/IFAX),
(Pull) 600 x 600

Scan for Fax: 600 x 600

Scan to Mobile Devices and Cloud-based Services

A range of solutions is available to provide scanning to compatible mobile devices and certain cloud-based services depending on your requirements.

Scan Speed (LTR)

Send: Automatic Colour Select "OFF" (300 x 300 dpi):

Single-Sided Scanning: 100 ipm

Double-Sided Scanning: 200 ipm

Automatic Colour Select "ON" (300 x 300 dpi):

Single-Sided Scanning: 50 ipm

Double-Sided Scanning: 100 ipm

Copy: Scan Speed priority (300 x 600 dpi):

Single-Sided Scanning: 50 ipm

Double-Sided Scanning: 100 ipm

Image Quality priority (600 x 600 dpi):

Single-Sided Scanning: 30 ipm

Double-Sided Scanning: 50 ipm

Send Specifications

Destination

Email/Internet Fax (SMTP), SMB v3.0, FTP, WebDAV, Mail
Box, Super G3 Fax, IP Fax (Optional)

Address Book

LDAP (2,000)/Local (1,600)/Speed Dial (200)

Send Resolution (dpi)

Push: Up to 600 x 600

Pull: Up to 600 x 600

Communication Protocol

File: FTP (TCP/IP), SMB v3.0, WebDAV

Email: SMTP, POP3

File Format

TIFF, JPEG, PDF (Compact, Searchable, Apply policy,
Optimize for Web, PDF A/1-b, Trace & Smooth, Encrypted,
Device Signature, User Signature), XPS (Compact,
Searchable, Device Signature, User Signature), Office
Open XML (PowerPoint, Word)

Fax Specifications

Maximum Number of Connection Lines

2

Modem Speed

Super G3: 33.6 Kbps
G3: 14.4 Kbps

Compression Method

MH, MR, MMR, JBIG

Resolution (dpi)

400x400 (Ultra Fine), 200x400 (Super Fine), 200x200 (Fine), 200x100 (Normal)

Sending and Recording Size

Statement to Legal

Fax Memory

Up to 30,000 Pages (2,000 jobs)

Speed Dials

Max. 200

Group Dials/Destinations

Max. 199 Dials

Sequential Broadcast

Max. 256 Addresses

Memory Backup

Yes

Store Specifications

Mail Box (Number Supported)

100 User In-boxes, 1 Memory RX Inbox, 50 Confidential Fax In-boxes, Maximum 10,000 Pages (2,000 jobs) Stored

Advanced Box

Communication SMB or WebDAV

Protocol:

Supported Windows (Windows 8.1/10)

Client PC:

Concurrent Connections (Max.)

SMB: 64

WebDAV: 3 (Active Sessions)

Advanced Box Available Disc Space

Approx. 16 GB

Security Specifications

Authentication

Standard: Universal Login Manager, uniFLOW Online Express,¹³ User Authentication, Department ID Authentication, Access Management System, Device and Function Level Log-in uniFLOW

Optional:

Data

Standard: Trusted Platform Module (TPM), Hard Disk Password Lock, Hard Disk Drive Erase, Mail Box Password Protection, Hard Disk Drive Encryption (FIPS140-2 Validated), Verify System at Startup,³ McAfee Embedded Control¹³

Optional: IEEE 2600.2 Common Criteria Certification, Data Loss Prevention (Requires uniFLOW)

Network

Standard: Encrypted Secure Print, IP/Mac Address Filtering, IPsec, TLS Encrypted Communication (v1.0/1.1/1.2/1.3), SNMP V3.0, IEEE 802.1X, IPv6, SMTP Authentication, POP Authentication before SMTP, S/MIME, SIEM Integration

Document

Standard: Secure Watermarks, Secure Print, Adobe LiveCycle® Rights Management ES2.5 Integration, Encrypted PDF, Encrypted Secure Print, Device Signature User Signatures

Optional:

Environmental Specifications

Operating Environment

Temperature: 10 to 30 °C

Humidity: 20 to 80% RH (Relative Humidity)

Power Requirements

110-127V AC 60 Hz, 6.9 A

Plug (Main Unit)

NEMA 5-15P

Power Consumption

Maximum: Approx. 1,500 W

Standby: Approx. 38.9 W¹⁴

Sleep Mode: Approx. 0.8 W or Less¹⁵

Typical Electricity Consumption (TEC) Rating¹⁶

C357iF: 0.36 kWh

C257iF: 0.25 kWh

Standards

ENERGY STAR® Certified

Consumables

Toner

NPG-58 Toner

Toner Yield (Estimated @ 5% Coverage)

Black: 23,000 Pages

Colour (C, M, Y): 18,000 Pages

- ¹ Subscription to a third-party cloud service required. Subject to third-party cloud service providers' Terms and Conditions.
- ² Third-party SIEM system required. Subject to third-party SIEM system's Terms and Conditions. Canon cannot ensure compatibility with all third-party SIEM systems.
- ³ This feature is off by default and must be turned on by the user. Warm-up times are affected once turned on.
- ⁴ Requires additional option.
- ⁵ Time from device power-on until copy ready (not print reservation).
- ⁶ Time from exiting Sleep Mode to when printing is operational.
- ⁷ Time from device power ON to when the copy icon appears and is enabled to operate on the touch panel display.
- ⁸ Includes consumables.
- ⁹ Requires the optional PCL International Font Set-A1.
- ¹⁰ Requires the optional Barcode Printer Kit-D1.
- ¹¹ Other operating systems and environments, including AS/400, UNIX, Linux, and Citrix may be supported. Some of these solutions are chargeable. SAP Device Types are available via the SAP Market Place. For more information, contact your authorized sales representative.
- ¹² Multi-Sheet Feed Detector Supported.
- ¹³ No charge for this solution; however, activation is required.
- ¹⁴ Reference value (measured one unit).
- ¹⁵ 0.8 W Sleep Mode not available in all circumstances due to certain settings.
- ¹⁶ Based on ENERGY STAR Product Specification for Imaging Equipment Version 3.0.

 WWW.CANON.CA



As an ENERGY STAR® Partner, Canon U.S.A., Inc. has certified these models as meeting the ENERGY STAR energy efficiency. ENERGY STAR and the ENERGY STAR mark are registered Canada trademarks. Canon, imageRUNNER, imageWARE, imagePASS, and the GENUINE logo are registered trademarks or trademarks of Canon Inc. in Canada and may also be registered trademarks or trademarks in other countries. Canon products offer certain security features, yet many variables can impact the security of your devices and data. Canon does not warrant that use of its features will prevent security issues. Nothing herein should be construed as legal or regulatory advice concerning applicable laws; customers must have their own qualified counsel determine the feasibility of a solution as it relates to regulatory and statutory compliance. McAfee and the McAfee logo are trademarks of McAfee LLC in Canada and/or other countries. All other referenced product names and marks are trademarks of their respective owners. All features presented in this brochure may not apply to all Series and/or products and may be optional; please check with your Canon Authorized Dealer for details. Product shown with optional accessories. Canon Canada does not provide legal counsel or regulatory compliance consultancy. Each customer must have its own qualified counsel determine the advisability of a particular solution as it relates to regulatory and statutory compliance. Specifications and availability subject to change without notice. Not responsible for typographical errors.

©2020 Canon Canada Inc. All rights reserved.

Federal Law prohibits copying of certain documents. Violators may be subject to penalties. We suggest that you check with your own legal counsel. Canon U.S.A., Inc. and Canon Canada, Inc. intend to cooperate with Law Enforcement Agencies in connection with claims of unauthorized copying.



 **McAfee**
PROTECTED

 **CANON**
GENUINE
TONER, CARTRIDGE
& PARTS



To learn about Canon's many awards, visit
www.canon.ca/awards.