

## imageRUNNER ADVANCE DX 6870i/6860i

imageRUNNER ADVANCE DX 6800 Series

Print up to 70 ppm (BW)

Scan up to 270/270 ipm (300 dpi) (BW/color, duplex)

Print up to 12" × 18"

6,350-sheet maximum paper capacity

Canon's comprehensive portfolio of imageRUNNER ADVANCE multifunction printers and integrated solutions can help **simplify** the end user experience and management of technology, better **control** sensitive information and print-related costs, and help ensure that technology investments proactively **evolve** with changing needs.





### WORKFLOW EFFICIENCY

- 10.1" intuitive touchscreen with smartphone-like usability.
- A unique, customized experience tailored to individual preferences using My ADVANCE.
- Supports mobile solutions and integration with many popular cloud services like Google Drive.<sup>1</sup>
- Scan and convert documents to searchable digital files in a variety of file formats.
- Integration with Canon and various third-party software with embedded application platform.
- Hot Folders allow users to drag and drop a file into a hot folder, and automatically print with predefined settings such as number of copies and finishing requirements.



### **SECURITY**

- Advanced standard security feature set to help safeguard sensitive information and assist in regulatory compliance.
- Integrates with existing, third-party SIEM\*.2 systems to help provide real-time, comprehensive insights into potential threats to the network and printers.
- Technology to verify that the device boot process, firmware, and applications initialize without alteration at startup. McAfee Embedded Control<sup>3</sup> utilizes a whitelist to protect against malware and tampering of firmware and applications.
- Security policy settings can be controlled with a dedicated password, configured from a central location, and exported to other supported devices.
- Control access to the device and specific features, using a host of flexible authentication methods—PIN code, user name/password, or card access.<sup>4</sup>



# QUALITY AND RELIABILITY

- Canon's signature reliability and engine technologies help keep productivity high and minimize the impact on support resources.
- Outstanding imaging technologies and toner allow for crisp text and consistent images in rich black-and-white tones.
- Designed to achieve maximum uptime with status notifications to help keep supplies replenished and intuitive maintenance videos for consumables replacement.
- imageRUNNER ADVANCE models have received many awards and recognition from leading industry analysts, often referencing strong reliability.

<sup>\*</sup> Security Information and Event Management



- Designed for quick, easy deployment.
- Remote diagnostics and parts life management for proactive maintenance and rapid fixes.
- Easy and intuitive to monitor device status and consumable levels, turn off devices remotely, observe meter readings, manage settings, and implement security policies.
- Common firmware and regular updates with Unified Firmware Platform (UFP) for continuous improvements and consistency across a fleet.



- Track and assess print, copy, scan, and fax usage and allocate costs to departments or projects.
- Apply print policies and restrict usage by user to help reduce unnecessary printing and contribute to cost efficiency.
- Standard cloud-based solution provides a centralized dashboard with up-to-theminute insights into printer activity.
- Upgrade to uniFLOW server or cloud-based solutions for full accounting and reporting for compatible Canon and third-party devices, pull printing, job routing, and powerful scan workflows.



### SUSTAINABILITY

- A combination of fusing technologies and low-melting-point toner minimizes power requirements and helps achieve low energy consumption.
- Encourage environmentally-conscious work practices by enabling multiple settings that can help save paper and energy.

### **CONFIGURATION OPTIONS**

## imageRUNNER ADVANCE DX 6800 Series



- · 2-tray, 3,250-sheet capacity
- · Corner and double stapling up to 50 sheets
- Supports Staple-free Stapling and Staple On Demand
- Supports optional internal 2/3-hole puncher (2/3 Hole Puncher Unit-A1)



### **BOOKLET FINISHER-AB1**

- 2-tray, 3,250-sheet capacity
- Corner and double stapling up to 50 sheets
- Booklet-making up to 20 sheets and saddle-folding up to 3 sheets
- Supports Staple-free Stapling and Staple On Demand
- Supports optional internal 2/3-hole puncher (2/3 Hole Puncher Unit-A1)



#### **INNER FINISHER-L1\***

- · 2-tray, 550-sheet capacity
- Corner and double stapling up to 50 sheets within the footprint of the main unit
- Supports Staple-free\*\* Stapling and Staple on Demand
- Supports optional internal 2/3-hole puncher (Ínner 2/3 Hole Puncher-D1)





#### HIGH CAPACITY CASSETTE **FEEDING UNIT-C1**

- 2,450-sheet capacity
- Supports up to Letter
- 14 lb. Bond to 140 lb. Index





**COPY TRAY KIT** 



### PAPER DECK UNIT-F1

- · 2,700-sheet capacity
- 14 lb. Bond to 140 lb. Index
- Supports Letter



### **CASSETTE FEEDING UNIT-AQ1**

- Two 550-sheet cassettes
- Supports up to 12" x 18"
- 14 lb. Bond to 140 lb. Index



- **INNER 2-WAY TRAY-M1**
- \* Inner Finisher-L1 not available on imageRUNNER ADVANCE DX 6870i. \*\* Staple-free stapling, up to ten pages of 17 lb. Bond.
- Required when Staple Finisher-AB1 or Booklet Finisher-AB1 is not installed.

#### Main Unit

Type

Monochrome Laser Multifunctional

Core Functions

Print, Copy, Scan, Send, Store Standard:

Optional: Control Panel

10.1" TFT LCD WSVGA Color Flat-panel

Memory 5.0 GB RAM

Solid State Drive 256 GB Standard: 1 TB Optional: Interface Connection

1000Base-T/100Base-TX/10Base-T, Network: Wireless LAN (IEEE 802.11 b/g/n)

Optional: Others

Standard: USB 2.0 (Host) x1, USB 3.0 (Host) x1,

NFC, Bluetooth Low Energy

USB 2.0 (Device) x1 Copy Control Interface Optional:

Paper Output Capacity (LTR, 20 lb. Bond) Standard: 250 Sheets Maximum: 3.450 Sheets

> (with Staple Finisher-AB1 or Booklet Finisher-AB1 and 3rd Copy Tray Kit-A1)

Paper Sources (LTR, 20 lb. Bond)

Dual 550-sheet Paper Cassettes, Standard:

100-sheet Stack Bypass

Dual 550-Sheet Paper Cassettes Optional:

(Cassette Feeding Unit-AM1), 2,450-Sheet High Capacity Paper Cassette (High Capacity Cassette Feeding Unit-C1), 2,700-Sheet Paper Deck

(Paper Deck Unit-F1) Paper Capacity (LTR, 20 lb. Bond)

Standard: 1,200 Sheets Maximum: 6,350 Sheets

**Finishing Capabilities** 

Standard:

Collate, Group Collate, Group, Offset, Staple, Saddle-Stitch, With Options:

Hole Punch, Staple Free Stapling, Staple On

Supported Media Types

Multi-Purpose Thin, Plain, Recycled, Color, Heavy, Coated, Tracing, Bond, Transparency, Label, Tray Pre-punched, Letterhead, Tab, Envelope

Paper Thin, Plain, Recycled, Color, Heavy, Bond, Transparency, Pre-punched, Letterhead, Cassettes:

Envelope6 Supported Media Sizes

Letter, Executive, Statement-R, Envelope Upper [No.10 (COM10), Monarch, DL, ISO-C5] Cassette:

Custom Size (3-7/8" x 5-7/8" to 11-3/4" x

12" x 18", 11" x 17", Legal, Letter, Letter-R, Lower Cassette: Executive, Statement-R, Envelope [No.10 (COM10), Monarch, DL, ISO-C5],

Custom Size (3-7/8" x 5-7/8" to 12" x 18") Multi-Purpose 12" x 18", 11" x 17", Legal, Letter, Letter-R, Executive, Statement, Statement-R, Tray

Envelope [No.10 (COM10), Monarch, DL, ISO-C5], Envelope Custom Size (3-7/8" x 3-1/2" to 12-5/8" x 18"), Custom Size/ Free Size (3-7/8" x 5-1/2" to 12-5/8" x 18")

Supported Media Weights

Cassettes: 14 lb. Bond to 140 lb. Index (52 to 256 g/m<sup>2</sup>) 14 lb. Bond to 140 lb. lindex (52 to 256 g/m²) 14 lb. Bond to 140 lb. Cover (52 to 300 g/m²) 14 lb. Bond to 140 lb. Index (52 to 256 g/m²) Stack Bypass: Duplexing:

Print/Copy Speed (BW)

Up to 70 ppm (Letter), up to 42 ppm 6870i

(Letter-R), up to 40 ppm (Legal), up to

35 ppm (11" x 17")

6860i Up to 60 ppm (Letter), up to 36 ppm

(Letter-R), up to 34 ppm (Legal), up to

32 ppm (11" x 17")

Warm-up Time

From Power Approx. 6 Seconds7

From Sleep Mode8

6870i: 7 Seconds or Less 6860i 6 Seconds or Less Quick Startup Approx. 4 Seconds9

Dimensions (W x D x H)

24-3/8" x 28-1/2" x 36-7/8" (620 x 722 x 937 mm)<sup>10</sup>

Installation Space (W x D)

44-7/8" x 45-3/4" (1,138 x 1,162 mm) Basic (Right Cover Open with Multi-purpose tray extended + Cassette Drawers Open)

Fully 73-1/2" x 45-3/4" (1,866 x 1,162 mm) Configured: (Staple Finisher-AB1 or Booklet Finisher-AB1 with the extension tray extended + Paper Deck Unit-F1 + Cassette Drawers open)

Weight11

6870i: Approx. 205 lb. (93 kg) 6860i: Approx. 200.6 lb. (91 kg)

## **Print Specifications**

Print Resolution (dpi)

1200 x 1200

Standard Page Description Languages

UFR II, PCL6, Adobe PS 3

Supported File Types PDF, TIFF, JPEG, EPS, 12 XPS

Printing from Mobile Devices and Cloud-based Services

A range of standard and optional software and MEAP-based solutions (including AirPrint, Mopria, Universal Print by Microsoft®, Canon PRINT Business, and uniFLOW Online) are available to provide printing from mobile devices or internet-connected devices and cloud-based services depending on your requirements. Please contact your sales representative for further information.

Fonts

PS.

PCI · 93 Roman, 10 Bitmap fonts, 2 OCR fonts, Andalé Mono WT J/K/S/T (Japanese,

Korean, Simplified and Traditional Chinese),13 Barcode Fonts<sup>14</sup>

Operating System<sup>15</sup>

UFRII/PS: Windows® 7/8.1/10/Server2008/

Server2008 R2/Server2012/Server2012 R2/Server2016/Server2019, Mac OS X

(10.11 or later)

136 Roman

PCL: Windows® 7/8.1/10/Server2008/ Server2008 R2/Server2012/Server2012

R2/Server2016/Server2019

PPD: Windows® 7/8.1/10, Mac OS X(10.10 or later)

## **Copy Specifications**

First-Copy-Out Time

6870i: Approx. 2.7 Seconds or Less 6860i: Approx. 2.9 Seconds or Less

Copy Resolution (dpi) 600 x 600

Multiple Copies Up to 9,999

Magnification

25%-400% (1% Increments)

Preset Reductions/Enlargements

25%, 50%, 64%, 73%, 78%, 100% (1:1), 121%, 129%,

200%, 400%

### **Scan Specifications**

Type

Single-Pass Duplexing Automatic Document Feeder

**Document Feeder Paper Capacity** Up to 200 Sheets (20 lb. Bond)

**Document Feeder Supported Media Sizes** 

11" x 17", Legal, Letter, Letter-R, Statement, Statement-R, Custom Size: 2-3/4" x 5-1/2" to 12" x 17"

**Document Feeder Supported Media Weights** 

Single-Sided 13.3 lb. Bond to 80 lb. Cover (50 to 220 gsm) Scanning: (BW, CL)
Double-Sided 13.3 lb. Bond to 80 lb. Cover (50 to 220 gsm)

Scanning: (BW. CL)

Platen Acceptable Originals Sheet, Book, 3-Dimensional Objects

Pull Scan

Color Network ScanGear2 for both Twain and WIA Windows® 7/8.1/10/Server 2008/ Supported Server 2008 R2/Server 2012/

Server 2012 R2/Server 2016

Scan Resolution (dpi) Scan for Copy: 600 x 600

Scan for Send: (Push) 600 x 600 (SMB/FTP/WebDAV/

IFAX), (Pull) 600 x 600

Scan for Fax: 600 x 600

Scan to Mobile Devices and Cloud-based Services

A range of solutions is available to provide scanning to compatible mobile devices and certain cloud-based services depending on your requirements.

Scan Speed (LTR) (BW/CL)

Single-sided 135/135 (300 dpi), 80/80 (600 dpi) Scanning: Double-sided 270/270 (300 dpi), 160/90 (600 dpi)

Scanning

## Send Specifications

Destination

Standard: E-mail/Internet FAX (SMTP), SMB3.0, FTP,

WebDAV, Mail Box Super G3 FAX, IP Fax

Optional: Address Book

LDAP (2,000)/Local (1,600)/Speed Dial (200)

Send Resolution (dpi)

Up to 600 x 600 Push: Up to 600 x 600 Pull-Communication Protocol

File: FTP(TCP/IP), SMB3.0 (TCP/IP), WebDAV

Email: SMTP, POP3

File Format

TIFF, JPEG, PDF (Encrypted, Compact, Standard:

Searchable, Apply Policy, Optimize for Web, User Signature, PDF A/1-b, Limited Color, Device Signature, User Signature), XPS (Compact, Searchable, Device Signature, User Signature), Office Open XML

(PowerPoint, Word)

### Fax Specifications (Optional)

Modem Speed

Super G3: 33.6 Kbps 14.4 Kbps Compression Method

MH, MR, MMR, JBIG Resolution (dpi)

 $400 \times 400$ ,  $200 \times 400$ ,  $200 \times 200$ ,  $200 \times 100$ 

Sending/Recording Size Statement-R to 11" x 17

Fax Memory

Up to 30,000 Pages (2,000 jobs)

Speed Dials Max. 200

Group Dials/Destinations

Max. 199 Dials

Sequential Broadcast Max. 256 Addresses

Memory Backup

### Store Specifications

#### Mail Box (Number Supported)

100 User In-boxes, 1 Memory RX In-box, 50 Confidential Fax In-boxes, Maximum 10,000 Pages (2,000 jobs) Stored

Communication Protocol: SMB or WebDAV

Supported

Client PC: Windows (Windows 8.1/10)

Concurrent Connections (Max.)

SMB: WebDAV:

#### Advanced Box Available Disc Space

Approx. 16 GB (Standard HDD) Approx. 480 GB (With Optional 1 TB HDD)

### **Security Specifications**

#### **Authentication and Access Control**

User Authentication (Picture Login, Picture and PIN Login, Card Login, Username and Password Login, Function Level Login, Mobile Login), Department ID Authentication (Department ID and PIN Login, Function Level Login), uniFLOW Online Express<sup>16</sup> (PIN Login, Picture Login, Picture and PIN Login, Card Login, Card and PIN Login, Username and Password Login, Department ID and PIN Login, Function Level Login), Access Management System (Access Control)

#### **Document Security**

Print Security (Secure Print, Encrypted Secure Print, Forced Hold Printing, uniFLOW Secure Print<sup>17</sup>), Receive Data Security (Confidential Fax Inbox Forwarding Received Documents Automatically), Scan Security (Encrypted PDF, Device Signature PDF/XPS, User Signature PDF/XPS, Adobe LiveCycle® Rights Management ES2.5 Integration), BOX Security (Mail Box Password Protected, Advanced Box Access Control), Send Data Security (Setting for requesting password input per transmission, Restricted E-mail/File send functions, Confirming FAX number, Allow/ Restrict Fax Driver Transmissions, Allow/Restrict Sending from History, S/MIME Support), Document Tracking (Secure Watermark)

#### **Network Security**

TLS 1.3, IPSec, IEEE802.1X authentication, SNMP V3.0, Firewall Functionality (IP/MAC Address Filtering), Dual Network Support (Wired LAN/Wireless LAN, Wired LAN/ Wired LAN), Disabling Unused Functions (Enabling/Disabling Protocols/Applications, Enabling/Disabling Remote UI, Enabling/Disabling USB Interface), G3 FAX separation from LAN, USB Port separation from LAN, Prohibit the execution of files stored in Advanced Box in the MFP, Scan and Send-Virus Concerns for E-mail Reception

Protecting SSD Data [SSD Data Encryption (FIPS140-2 Validated), SSD Lock, Standard SSD Initialize, Trusted Platform Module (TPM), Job Log Conceal Function, Protecting MFD Software Integrity, Checking MFD Software Integrity (Verify System at Startup, Runtime Intrusion Detection)

#### **Device Management and Auditing**

Administrator Password, Digital Certificate and Key Management, Audit Log, Cooperating with External Security Audit System (Security Information and Event Management), Image Data Logging, Security Policy Setting

### **Environmental Specifications**

#### **Operating Environment**

Temperature: 50 to 86° F

Humidity: 20 to 80% RH (Relative Humidity)

#### **Power Requirements** 110-127V, 60Hz, 12A

#### Power Consumption

Approx. 1,800 W Maximum: Approx. 48.4 W18 Standby: Sleep Mode: Approx. 0.8 W<sup>19</sup>

Typical Electricity Consumption (TEC) Rating:20

6870i: 0.89 kWh 6860i: 0.74 kWh

#### Standards

ENERGY STAR® Certified

### Consumables

#### Toner

GPR-63 Toner BK

#### Toner Yield (Estimated @ 6% Coverage)

GPR-63 Toner: 71,500 Pages

- <sup>1</sup> Subscription to a third-party cloud service required. Subject to third-party cloud service providers' Terms and Conditions.
- <sup>2</sup> Third-party SIEM system required. Subject to third-party SIEM system's Terms and Conditions. Canon cannot ensure compatibility with all third-party SIEM systems.
- <sup>3</sup> This feature is off by default and must be turned on by the user. Warm-up times are affected once turned on.
- 4 Requires additional option
- <sup>5</sup> Finishing capabilities vary depending on the options connected.
- <sup>6</sup> Envelope Feeder Attachment (standard) is required.
- <sup>7</sup> Time from device power-on, until copy ready (not print reservation)
- <sup>8</sup> Time from exiting Sleep mode to when printing is operational.
- <sup>9</sup> Time from device power-on to when the copy icon appears and is enabled to operate on the touch panel display
- 10 Includes main unit and standard ADF
- Includes main unit, consumables, and Cassette Feeding Unit-AQ1.
- <sup>12</sup> EPS can be printed directly only from the Remote User Interface.
- 13 Requires the optional PCL International Font Set-A1.
- 14 Requires the optional Barcode Printer Kit-D1
- Other operating systems and environments, including AS/400, UNIX, Linux, and Citrix may be supported. Some of these solutions are chargeable. SAP Device Types are available via the SAP Market Place. For more information, contact your sales representative.
- <sup>16</sup> No charge for this solution; however, activation is required.
- 17 Requires uniFLOW Online/uniFLOW
- <sup>18</sup> Reference Value (measured one unit).
- $^{\rm 19}$  0.8 W Sleep mode not available in all circumstances due to certain settings.
- <sup>20</sup> Based on ENERGY STAR® Product Specification for Imaging













As an ENERGY STAR® Partner, Canon U.S.A., Inc. has certified these models as meeting the ENERGY STAR energy efficiency. ENERGY STAR and the ENERGY STAR mark are registered Canada trademarks. Canon, imageRUNNER, imagePASS, and the GENUINE logo are registered trademarks or trademarks of Canon Inc. in Canada and may also be registered trademarks or trademarks in other countries. Canon products offer certain security features, yet many variables can impact the security of your devices and data. Canon does not warrant that use of its features will prevent security issues. Nothing herein should be construed as legal or regulatory advice concerning applicable laws; customers must have their own qualified counsel determine the feasibility of a solution as it relates to regulatory and statutory compliance. McAfee and the McAfee logo are trademarks of McAfee LLC in Canada and/or other countries. All other referenced product names and marks are trademarks of their respective owners. All features presented in this brochure may not apply to all Series and/or products and may be optional; please check with your Canon Authorized Dealer for details. Product shown with optional accessories. Canon Canada does not provide legal counsel or regulatory compliance consultancy. Each customer must have its own qualified counsel determine the advisability of a particular solution as it relates to regulatory and statutory compliance. Specifications and availability subject to change without notice. Not responsible for typographical errors.

©2021 Canon Canada Inc. All rights reserved.









Camon

